Hilumz®
The Professional's LED Choice

HRSII RipStrips II Specification Sheet

OVERVIEW

- Troffer LED Upgrade

2023 Technology | Low Glare, URG <22
160 Lumens / Watt

- 5-Minute Magnetic Install
- Optimize Conversion to LED
- Wattage Field Adjustable
- CCT (35K, 40K, 50K) Field Adjustable

APPLICATION

Designed for Troffers:

- Office
- School
- Medical
- Grid ceiling height of 8 to 16 feet
- 3500K, 4000K, 5000K
- Various power options for ceiling height

FEATURES

Ease of Install

- Faster install than ballast bypass tubes
- Magnetic backed strips and driver; driver needs a single tack screw
- Quick connect plug and play

Excellent Light

- CRI >83 for interior color clarity
- Flicker-free, hum-free, buzz-free
- Available in variety of wattages for various application heights
- Standard 0-10V control enabled dimming

Long Lasting

- Large, metal case housing driver that promotes airflow to critical components
- Overpopulated LED board
- Eliminates failure points from the system; ballasts, tombstones

DLC QPL LISTED

5 YEAR WARRANTY

ETL LISTED c US Intertek

HRSII RipStrips II Specification Sheet

PERFORMANCE SPECIFICATIONS

Product	Kit	Selectable Wattage Driver	Lumens @4000k	CCT/Color	Input Voltage	Dimming
HRS2	14 (1x4: 1, 4' strip 22 (2x2: 2, 2' strips) 32 (3x2: 3, 2' strips)	15 Watts	2385	3500K 4000K 5000K Selectable	120-277VAC	0-10V
		20 Watts	3100			
		25 Watts	3800			
	24 (2x4: 2, 4' strips) 18 (1x8, 2, 4' strips) 34 (3x4: 3, 4' strips)	24 Watts	3,800			
		30 Watts	4,850			
		40 Watts	6,200			
	44 (4x4: 4, 4' strips)	40 Watts	6,360			
		50 Watts	7,750			
		60 Watts	9,120			

Installed in troffers for DLC qualification
Installation instructions should be correctly followed to ensure code compliance
Driver includes wattage adjustable toggle switch for various power outputs

Wattage & CCT Adjustable Toggle

Individual Kit Case

ORDERING

Example **HRS2-24-ADJ:** Two four foot strips with 24/30/40 adjustable driver with no controls

Product	Size	Wattage	Packaging
HRS2	14 (1x4: 1, 4' strip) 22 (2x2: 2, 2' strips) 32 (3x2: 3, 2' strips) 24 (2x4: 2, 4' strips) 18* (1x8: 2, 4' strips) 44 (4x4: 4, 4' strips) 34 (3x4: 3, 4' strips)	ADJ (adjustable)	B - Bulk K - Individual Kit

All strips are 3500K, 4000K, 5000K selectable

* 1x8 includes a standard wire harness and a 4' wire handness to extend to the second strip

HILUMZ USA

6835 Shiloh Rd E
Suite C8
Alpharetta, GA 30005

sales@hilumzusa.com
678-867-9200
hilumzusa.com